

# DAG1000-4S(GE) FXS Analog VoIP Gateway

## Overview

DAG1000-4S(GE) is a multi-functional VoIP gateway with 1000Mbps of full duplex connection through its combo copper/ SFP uplinks. The gateway offers 2 fast ethernet ports, 1 SFP port and 4 FXS RJ11 Telephone ports, which helps to seamless connectivity between IP-based telephony networks and legacy telephones (POTS), fax machines and PBX systems. It is ideally suited for active FTTx application, small and medium businesses, service providers and multi-location environments that need VoIP services.

DAG1000-4S supports the standard SIP protocol and it's compatible with leading IMS/NGN platforms and SIP-based IP telephony systems.

## Key Features

- Cost effective gateway with 4 FXS ports
- Combo copper / SFP slot interface runs 1000Mbps (Gigabit) on up-link port
- Fax over IP (T.38 and Pass-Through)
- Support IPv4 and IPv6
- TR069 and SNMP
- Multiple codecs: G.711A/U,G.723.1,G.729A/B, iLBC
- Fully compatible with leading IMS/NGN, SIP based IP telephony system

**DAG1000-4S(GE)**



## Physical Interfaces

### Capacity

4 FXS, RJ11

### Ethernet Interfaces:

1\* WAN, 100/1000Mbps, RJ-45

1\* LAN, 100/1000Mbps, RJ-45

1\* SFP Slot (uplink port)

## Voice & FAX

G.711A/U law, G.723.1, G.729A/B, G.726, iLBC

Silence Suppression

Comfort Noise Generation(CNG)

Voice Activity Detection(VAD)

Echo Cancellation(G.168), with up to 128ms

Adaptive (Dynamic) Jitter Buffer

Hook Flash

Programmable Gain Control

T.38/Pass-through

High speed fax up to 14.4kbps

Modem/POS

DTMF mode: Signal/RFC2833/INBAND

VLAN 802.1P/802.1Q

(Voice/data/management VLANs)

Layer3 QoS and DiffServ

## Supplement Service

Call Waiting

Blind Transfer

Attend Transfer

Call Forward on Busy

Call Forward on No Reply

Unconditional Call Forward

Warm/Immediately Hotline

Call Hold

Do-not-disturb

3-Way Conference

Message Waiting Indicator

Speed Dial

## FXS

Connector: RJ11

Dial Mode: DTMF and Pulse

Pulse: 10 and 20 PPS

Caller ID: DTMF/FSK CLI Presentation

Max Cable Length: 3KM

Reversed Polarity

Programmable Call Progress Tone

## Software Features

Hunting Group

Web ACL

Telnet ACL

Action URL

PPPoE/IPv4/IPv6

OpenVPN

Digitmap

Routing Rules based Prefixes

Caller/Called Number Manipulation

## Maintenance

SNMP v1/v2/v3

TR069, TR181

Auto Provisioning

Web/Telnet

Configuration Backup/Restore

Firmware Upgrade via Web

CDR

Syslog(Emerg,alert, critical,error warning,notice,info, debug)

Ping/Tracert Test

Network Capture

Outward Test(GR909)

NTP/Daylight Saving Time

IVR local Maintenance

Cloud-based Management

## VoIP

### Protocol:

SIP v2.0 (UDP/TCP),RFC3261

SDP,RTP(RFC2833), RFC3262,

3263,3264,3265,3515,2976,3311

ETC (3GPP TS24.629), 3891,3892

SIP over TLS

RTP/SRTP/RTCP, RFC2198, 1889

RFC4028 Session Timer

RFC3266 IPv6 in SDP

RFC2806 TEL URI

RFC3581 NAT,rport

Primary/backup SIP server

Outbound Proxy

DNS SRV/ A Query/NATPR Query

SIP Trunk

Early Media/Early Answer

NAT:STUN, Static/Dynamic NAT

## Environmental

### Power Supply:

100-240VAC, 50-60 Hz@DC12V 1A

Power Consumption:5W(Typical)

Storage Temperature: -20 °C ~80 °C

Humidity:10%-90% Non-Condensing

Dimensions(W/D/H): 170\*118\*25mm

Unit Weight: 0.5kg

## Shenzhen Dinstar Co.,Ltd.

Floor 18, Building 7A, Vanke Cloud City Phase 1, Xingke 1st Street, Xili Sub-district, Nanshan District, Shenzhen, P.R. China 518000

www.dinstar.com  
sales@dinstar.com



## About Us

Founded in 2011 in Shenzhen, DINSTAR is a leading global provider of IP Unified Communication products including VoIP Gateways, IP PBXs, IP Phones and SBCs, we have been delivering more agile, efficient and affordable communication solutions and unparalleled communication experiences to our customers with our reliable, innovative and future-proof products for years. Through our value-added distributors and resellers worldwide, now DINSTAR serves telecom operators, service providers, system integrators, enterprises, SMBs and OEM partners in over 100 countries.